



## OptiNID® 300 Series Optical Demarcation Slack Storage Closure

The OptiNID (OPN) 300 series are optical demarcation closures designed for use in either indoor or outdoor environments. Smaller to suit FTTH demarcation applications, the OPN-327SS and the OPN-350SS are equipped to handle up to two adapters each. Configured with routing rings positioned to accommodate safe slack storage, the OPN-300 series closures can be either wall or pole-mounted for ease of use and accessibility.

### Features

- Weather-resistant thermoplastic alloy
- Self-latching, hinged cover design allows easy access without loose parts
- Routing rings positioned for safe slack storage
- Capacity for up to two adapters
- Ground stud provided in the OPN-350SS



OPN-327SS



OPN-350SS

### Specifications

PARAMETER	VALUES
Dielectric Strength	Minimum 2500 Vrms for 1 minute
Impact Test	-40°F (-40°C), 5 ft-lbs on all external surfaces
Drop Test	-40°F (-40°C), 5 ft onto concrete surface four times
Rain	24 hours at 10 psi
UV Resistance (Days Exposed)	60 per ASTM-G26-84
Salt Fog (Days Exposed)	60 per ASTM-BLL7-90
Flammability	UL94-5V
Chemical Resistance 30 Days at 100°F and 95% RH	Resists chipping and/or cracking when subject to house paint, wasp spray, sulfuric acid, kerosene and sodium hydroxide
Material	UL® listed flame retardant thermoplastic alloy
Dimensions (H x W x D) in. (cm)	6.3 x 7.8 x 2.0 (15.7 x 19.7 x 5.0)
Cable Entrance in. (cm) diameter - Input	1 x 3/4" NPT (1.130"), 2 x 1/2" NPT (0.875")
Covers	Standard, molded-in snap finger and "F" termination
Operating Temperature Range – °F (°C)	-40 to 140 (-40 to 60)

### Ordering Information

DESCRIPTION	AFL NO.
<b>BASE PRODUCT</b> <sup>1,2</sup>	
OptiNID OPN-327SS Slack Storage Box, 1 x SC/APC Adapter	DM000720
OptiNID OPN-350SS Slack Storage Box, 1 x SC/APC Adapter, Splice Chip, Ground Stud	DM000795
<b>ACCESSORIES</b> <sup>3</sup>	
Heyco M3234 Compression Fitting, 18 mm to 11 mm Grip (includes 4) – Left Port Only	DM001171

#### Notes:

1. All standard OPN-300 Series configurations come equipped with a 3/4" NPT fitting, rubber grommet and Heyco M4519 compression fitting.
2. Contact AFL customer service for additional configurations.
3. See OptiNID Accessory Page for additional kits.